

A4 - Hummingbird

Automatic Dispenser



- ➡ Super High Accuracy: 1/2000Y
- ➡ 100% Recirculation
- ➡ Suitable for Sample Paint Dispensing

● Electrical Can Table Version

SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Lageweg 35 - J, 2222 AG
Katwijk The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: ul. Postepu 19. mag.5
02-676 Warszawa Polska
Email: gianni.capozzi@santint.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 220, Glendale Heights,
IL 60139, U.S.A
Email: frank@santint.com

SANTINT • AUSTRALIA

Add: 3 Technology Circuit
Hallam Victoria, Australia
Email: Info.AU@santint.com

A4 - Hummingbird FEATURES >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



Manual Can Table Version

1 Patented Double Pump Double Nozzle

1/2000Y Minimum Shot



2 100% Recirculation

Zero nozzle dryness/blockage;
purge-free;
maintenance-free;
colorant saving;
stable accuracy.



3 Box Tinting

Saving PC cost;
pre-installed software,
shorter installation time.



4 Calibration-free Piston Pump



5 打孔器可选

(电动平台版)



P1.1 Piston Pump
Sequential Dispensing

■ Minimum Shot
1/2000Y(0.015ml)

■ Flow Rate 900ml/min

■ Efficiency 300ml/min

■ Pump Capacity 100ml

■ Stirring Speed 20rpm

■ Canister Size 1.8L / 2.3L POM
2.3L / 3.8L Stainless Steel (Optional)
■ NO. of Canisters Up to 16

■ Optional Electrical Can Table

■ Max Can Size (D X H) Manual 320X500mm
Electrical 350X470mm

■ Machine Dimension (W X D X H) 707X848X1270mm

■ Packing Dimension (W X D X H) 830X990X1500mm

Loading Quantity 14 Pieces/20"Container

■ Net Weight Electrical 160Kg, Manual 140kg

■ Power ≤ 100W

■ Gross Weight Electrical 185Kg, Manual 165Kg

■ Power Supply 220V/110V 50Hz/60Hz

A4 - Hummingbird

Technical Parameters